

X303W

Business Phone



The Elevate X303W is a high - performance desk phone for businesses seeking a reliable and efficient communication solution. Equipped with a vibrant color screen, 3 line keys, and built-in Wi-Fi, the X303W provides a cost-effective and quality communication solution.

Highlights

- 2.4" inch 320x240 pixel color screen
- Support audio codec G.722 and Opus, HD audio on speakerphone and handset
- Support 6-party local conference
- Built-in 2.4/5 GHz Wi-Fi

ELEVATE X303W BUSINESS PHONE PRODUCT SPECIFICATIONS

Generic:

- 4 SIP Lines
- HD Voice
- PoE Enabled
- 2.4/5 GHz Wi-Fi
- 2.4-inch color screen
- Handset / Hands-free / Headset mode
- Desktop Stand / Wall mountable (need additional parts)
- Optional external power supply

Phone Features:

- Local Phonebook (1000 entries)
- Remote Phonebook (XML/LDAP, 1000 entries)
- Call logs (In/Out/Missed, 600 entries)
- Blocked List/Allowed List
- Screen saver
- Voice Message Waiting Indication (VMWI)
- Programmable DSS/Soft keys
- Network Time Synchronization
- Built-in Wi-Fi
 - 2.4 GHz 802.11 b/g/n
 - 5 GHz, 802.11 a/n/ac
- Support Plantronics wireless headset (Through Plantronics APD-80 EHS Cable)
- Voice Activity Detection (VAD) / Comfort Noise Generation (CNG)
- / Background Noise Estimation (BNE) / Noise Reduction (NR) /
- Automatic Gain Control (AGC)
- Packet Loss Concealment (PLC)
- Dynamic Adaptive Jitter Buffer
- DTMF: In-band, Out-of-Band (RFC2833/ SIP INFO)

Audio:

- HD Voice Microphone/Speaker (Handset/Hands-free, 0 ~ 7 KHz frequency response)
- Wideband ADC/DAC 16KHz Sampling
- Narrowband Codec: G.711a/u, G.729A

- Wideband Codec: G.722, Opus
- Full-duplex Acoustic Echo Canceller (AEC)
- Syslog

Network:

- Physical: 10/100 Mbps Ethernet, dual bridged port for PC bypass
- IP Mode: IPv4/IPv6
- IP Configuration: Static IP / DHCP / PPPoE
- Wi-Fi Encryption: WPA /WPA2-PSK /802.X EAP
- Network Access Control: 802.1x
- VPN: L2TP / OpenVPN
- VLAN
- LLDP
- QoS
- RTCP-XR (RFC3611), VQ-RTCPXR (RFC6035)

Protocols:

- SIP 2.0 over UDP/TCP/TLS
- RTP/RTCP/SRTP
- STUN
- DHCP
- IPv6
- LLDP
- PPPoE
- 802.1x
- L2TP
- Open VPN
- SNTP
- FTP/TFTP
- HTTP/HTTPS
- TR-069
- AES128 & AES256

ELEVATE X303W BUSINESS PHONE PRODUCT SPECIFICATIONS

Deployment & Management:

- Auto-Provisioning via FTP/TFTP/HTTP/HTTPS/DHCP
OPT66/SIP PNP/TR-069
- Web Management Portal
- Web-based Packet Dump
- Configuration Import/Export
- Phonebook Import/Export
- Firmware

Physical Specifications:

- LCD: 2.4 inch (320x240) Color Screen
- Keypad: 36 keys, including
 - 4 Soft-keys
 - 9 Function keys (Hold/Transfer/Voice
message/Conference/Phonebook
/MWI/Headset/Redial/Hands-free)
 - 3 Line keys (With LED Indicator Light)
 - 4 Navigation keys
 - 1 OK key
 - 12 Standard Phone Digit keys
 - 3 Volume Control keys (Up/Down/Mute (Microphone))
- Handset (RJ9) x1
- Standard RJ9 Handset Wire x1
- 1.5M CAT.5E Ethernet Cable x1
- Desktop stand x1
- Status Indicator Light x1 (Red)
- RJ9 Port x2: Handset x1, Headset x1
- RJ45 Port x2: Network x1, PC x1 (Bridged to Network)
- Security Slot x1
- DC Power Input: DC5V / 1A

- Power Consumption(Adapter): 1.218~2.39W
- Power Consumption(PoE): 2.12~3.49W
- Working Temperature: 0~45
- Working Humidity: 10~95%
- Installation:
 - Desktop Stand
 - Wall-mounted (need additional parts)
- Color: Black
- N.W/CTN: 8.98kg
- G.W/CTN: 9.69kg
- Device Dimensions:
 - Desktop Stand (45°): 169x201.1x177.4 mm
 - Desktop Stand (50°): 169x191.9x185.8 mm
 - Wall-mounted: 169x120.1x213.7 mm
- Gift Box Dimensions: 250x220x55mm
- Outer CTN Dimensions: 460x300x270mm(10 PCS)

QUESTIONS? CONTACT US TODAY!